


KB5004



Capacitive sensor

KB-3020-BPKG/NI



Product characteristics

Electrical design		PNP
Output function		normally open
Sensing range	[mm]	3...20
Housing		cylindrical
Dimensions	[mm]	Ø 34 / L = 81

Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	13; (24 V)
Protection class		II
Reverse polarity protection		yes

Outputs

Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2,5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	40
Short-circuit proof		yes
Overload protection		yes

Detection zone

Sensing range	[mm]	3...20
Sensing range adjustable		yes
Factory setting sensing range	[mm]	20
Real sensing range S_r	[mm]	$20 \pm 10 \%$
Operating distance	[mm]	0...16,2

Accuracy / deviations

Correction factor		glass: 0,4 / water: 1 / ceramics: 0,2 / PVC: 0,2
Hysteresis	[X01]	1...15
Switch point drift	[X01]	-15...15

KB5004




Capacitive sensor

KB-3020-BPKG/NI

Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 65
Increased immunity		yes; (increased immunity to conducted radio frequency interference)
Tests / approvals		
EMC		EN 60947-5-2
MTTF	[ANN]	778
Mechanical data		
Weight	[g]	255,5
Housing		cylindrical
Mounting		non-flush mountable
Dimensions	[mm]	Ø 34 / L = 81
Materials		PBT
Displays / operating elements		
Display		switching status 1 x LED, yellow
Accessories		
Accessories (supplied)		Mounting clamps: 1 screwdriver: 1
Remarks		
Pack quantity		1 pcs.

Electrical connection
Cable: 2 m, PVC; 3 x 0,5 mm²

Connection



- Core colours :
- BN = brown
 - BU = blue
 - BK = black